



C1 Series Downlight

	Cutout:80mm-85mm Cutout:105mm-110mm	Cutout:80mm-85mm Cutout:105mm-110mm	Cutout:80mm-85mm Cutout:105mm-110mm	
8W/10W 12W/15W/20W				15° 24° 30° 36° 45°
C119 IP42 Anti-fog Downlight				

<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div>				
				
Model	PBL-C119R-S-3	PBL-C119R-S-4		
LED Chip	CREE	CREE		
LED Power	8W/10W/12W/15W	12W/15W/20W		
CCT	2700-5000K	2700-5000K		
CRI	Ra>80/90	Ra>80/90		
Beam angle	15°/24°/30°/36°	15°/24°/30°/36°		
Size	90mm*112mm	118mm*130mm		
Cutout	75mm-80mm	105mm-110mm		
				
Model	PBL-C119R-O-3	PBL-C119R-O-4		
LED Chip	CREE	CREE		
LED Power	8W/10W/12W/15W	12W/15W/20W		
CCT	2700-5000K	2700-5000K		
CRI	Ra>80/90	Ra>80/90		
Beam angle	15°/24°/30°/36°	15°/24°/30°/36°		
Size	90mm*112mm	118mm*130mm		
Cutout	75mm-80mm	105mm-110mm		
				
Model	PBL-C119R-P-3	PBL-C119R-P-4		
LED Chip	CREE	CREE		
LED Power	8W/10W/12W/15W	12W/15W/20W		
CCT	2700-5000K	2700-5000K		
CRI	Ra>80/90	Ra>80/90		
Beam angle	15°/24°/30°/36°	15°/24°/30°/36°		
Size	90mm*112mm	118mm*130mm		
Cutout	75mm-80mm	105mm-110mm		
Option				
Finish				
Body	  			
Optics				
Reflector				
Dim Type	-TRIAC -0-10V -1-10V -DALI -Others			
Lighting Efficiency	Nomal:50-65lm/w			