



J4 Series Track

	PBL-J409R-A-80	PBL-J409R-A-96	PBL-J409R-B-80	PBL-J409R-B-96	PBL-J409R-C-80	
J409-A Top-mounted Spotlight						15°/20° 30°/36°/45°
J409-B Side-mounted Spotlight						
J409-C Recessed Spotlight						
	20W/25W/30W	30W/35W/40W 50W	20W/25W/30W	30W/35W/40W 50W	20W/25W/30W	



Model	PBL-J409R-A-80	PBL-J409R-A-96
LED Chip	CREE CITIZEN	CREE CITIZEN
LED Power	20W/25W/30W	30W/35W/40W/50W
CCT	2700K-5000K	2700K-5000K
CRI	Ra>80/90	Ra>80/90
Beam Angle	15°/20° 30°/36°/45°	15°/20° 30°/36°/45°
Size	164mm*130mm*80mm	213mm*165mm*96mm
Phase	1/2/3 Phase	1/2/3 Phase






Model	PBL-J409R-B-80	PBL-J409R-B-96
LED Chip	CREE CITIZEN	CREE CITIZEN
LED Power	20W/25W/30W	30W/35W/40W/50W
CCT	2700K-5000K	2700K-5000K
CRI	Ra>80/90	Ra>80/90
Beam Angle	15°/20° 30°/36°/45°	15°/20° 30°/36°/45°
Size	180mm*130mm*80mm	188mm*165mm*96mm
Phase	1/2/3 Phase	1/2/3 Phase



Model	PBL-J409R-C-80
LED Chip	CREE CITIZEN
LED Power	20W/25W/30W
CCT	2700K-5000K
CRI	Ra>80/90
Beam Angle	15°/20° 30°/36°/45°
Size	100mm*130mm*190mm
Cutout	90mm-95mm

Option

Finish

Body   

Phase



Connector



Dim Type

-TRIAC
-DALI
-Others

Lighting Efficiency

Normal:80-85lm/w
Custom:90-100lm/w